

REVADER®



TROJAN AUXILIARY PTZ CAMERA

62150M-02

TROJAN AUXILIARY PTZ CAMERA

Our Trojan Auxiliary PTZ Camera is a compact, rugged, PoE 4MP PTZ redeployable camera with infra-red.



The **Revader Trojan Auxiliary PTZ Camera** works in conjunction with the Trojan redeployable camera, enabling a second PTZ camera, by utilising the functionality of the Trojan's PoE out facility.

Flexible to your requirements, the Trojan Auxiliary PTZ Camera is **straightforward to install** in virtually any location, and can be rapidly repositioned to respond to changing security demands. Video footage is saved to on-board edge storage on the host Trojan Redeployable Camera and can be controlled and monitored individually via a **low-bandwidth link**, and downloaded remotely in HD quality, via wired, wireless and mobile networks.

The Trojan with its Auxilliary Camera together with other accessories can operate on a **standalone basis or can be networked together with other Trojans** and controlled from any number of remote locations. They also perform highly when integrated into existing CCTV systems and interface with a range of software platforms.

TROJAN AUXILIARY PTZ CAMERA

All Revader redeployables use our unique **EasyFit bracket system** as standard, and can also be permanently fixed to poles, walls, fences or trees.

Mechanical

Chassis	Aluminum Alloy
Surface	2-pack polyurethane paint light/dark grey
Connectivity	Water and dust resistant IP68, circular connector.
Dimensions	250mm x 178mm Diameter
Fixing Dimensions	2 x 5mm holes @ 25mm pitch
Weight	3.5kgs
Durability	Vandal-resistant IP66
Working Temperature	-30°C to 60°C

Camera & Lens

Camera Type	Ruggedised PTZ
Min. Illumination	0.005Lux Colour 0.001 Lux IR ON /Black and white.
Lens	f=4.8 to 120mm (F1.6~F3.5)
Resolution	2560(H) x 1440(V)
Coverage	360°Endless PTZ
Zoom	25x optical 16 x Digital
PTZ Devices	Full 3-axis control
Day and Night	Removable IR-cut filter for day & night Intelligent IR range of 50 meters
Part No.	62150

E&OE